

AD-A253 809



N PAGE

Form Approved
OMB No 0704-0188

(2)

Public reporting burden of this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 07/92		3. REPORT TYPE AND DATES COVERED POP Test (06/92)	
4. TITLE AND SUBTITLE Performance Oriented Packaging Testing of Container, Shipping and Storage, for Mk 125 Mod 2 RATO Rocket Motor for Packing Group II Solid Hazardous Materials				5. FUNDING NUMBERS DTIC ELECTE S A D AUG 3 1992	
6. AUTHOR(S) Victor D. Saul					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Weapons Station Earle Test and Evaluation Branch (Code 5023) Colts Neck, NJ 07722-5000				8. PERFORMING ORGANIZATION REPORT NUMBER DODPOPHM/USA/DOD/NADTR92019	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Commander, Naval Surface Warfare Center, Indian Head Division (Code 5710-T), 101 Strauss Avenue, Indian Head, MD 20640-5035				10. SPONSORING/MONITORING AGENCY REPORT NUMBER Same as above	
11. SUPPLEMENTARY NOTES N/A					
12a. DISTRIBUTION/AVAILABILITY STATEMENT This document has been approved for public release and sale; its distribution is unlimited.			12b. DISTRIBUTION CODE		
13. ABSTRACT (Maximum 200 words) This Performance Oriented Packaging (POP) test was conducted to ascertain whether the Shipping and Storage Container for Mk 125 Mod 2 RATO Rocket Motor meets the Packing Group II requirements specified by the United Nations Recommendation on the Transportation of Dangerous Goods Document, ST/SG/AC.10/1, Revision 6, Chapters 4 and 9 and the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 1 October 1991. The packaged commodity used for the test was a simulated load of sand weighing 10 kg (22 pounds). This represents the current maximum commodity weight. To compensate for future growth variations in product and/or packaging, 1 kg (2 pounds) were added. Gross weight of the loaded container was 16 kg (35 pounds). The test results indicate that the container has conformed to the POP requirements.					
14. SUBJECT TERMS POP Test of Shipping and Storage Container for Mk 125 Mod 2 RATO Rocket Motor				15. NUMBER OF PAGES 7	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED		18. SECURITY CLASSIFICATION OF THIS PAGE UL		19. SECURITY CLASSIFICATION OF ABSTRACT UL	
				20. LIMITATION OF ABSTRACT UL	

DODPOPHM/USA/DOD/NADTR92019

**PERFORMANCE ORIENTED PACKAGING TESTING
OF
CONTAINER, SHIPPING AND STORAGE,
FOR ROCKET MOTOR, RATO, MK 125 MOD 2
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS**

Author:
Victor D. Saul
Mechanical Engineering Technician

Performing Activity:
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5000

Accession For	
NTIS CRARI	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Dist. Branch	
Date	
Dist	Aviation Special
A-1	

July 1992

DTIC QUALITY INSPECTED 5

FINAL

92-20928



DISTRIBUTION UNLIMITED

Sponsoring Organization:
Naval Surface Warfare Center
Indian Head Division (Code 5710-T)
Indian Head, MD 20640-5035

INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the Shipping and Storage Container for Mk 125 Mod 2 RATO Rocket Motor (Packing Group II) meets the requirements specified by the United Nations Recommendation on the Transportation of Dangerous Goods Document, ST/SG/AC.10/1, Revision 6, Chapters 4 and 9 and the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 1 October 1991. The packaged commodity used for the test was a simulated load of sand weighing 10 kg (22 pounds). This represents the current maximum commodity weight. To compensate for future growth variations in product and/or packaging, 1 kg (2 pounds) were added. Gross weight of the loaded container was 16 kg (35 pounds). The containers were identified as #1, #2, and #3.

TESTS PERFORMED

1. Base Level Vibration Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.608. Containers #1, #2, and #3 were placed on a repetitive shock platform which has a vertical linear motion of 1-inch double amplitude. Movement of the containers were restricted during vibration in all but the vertical direction. The frequency of the platform was increased until the containers left the platform 1/16 of an inch at some instant during each cycle. Test time was 1 hour.

2. Stacking Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.606. Containers #1, #2, and #3 were used for this test. Each container was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a minimum height of 3 meters (including the test container). A weight of 47.89 kg (105.6 pounds) was stacked on each test container. The test was performed for 24 hours. The weight was then removed and the containers examined.

3. Drop Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.603. Six drops were performed from a height of 1.2 meters (4 feet) in the following orientations (three drops for each orientation):

- a. Horizontally using container #1, #2, and #3.
- b. Diagonally on the edge between the cover assembly and the top ring of the container using container #1, #2, and #3.

PASS/FAIL

1. Base Level Vibration Test

The criteria for passing the base level vibration test is outlined in Title 49 CFR, Sec. 178.608(c): No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength.

2. Stacking Test

The criteria for passing the stacking test is outlined in Title 49 CFR, Sec. 178.606(d): No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, cause instability in stacks of packages, or cause damage to inner packagings likely to reduce safety in transportation.

3. Drop Test

The criteria for passing the drop test is outlined in Title 49 CFR, Sec. 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested, no rupture occurs which would permit spillage of loose explosive substances or articles from the outer packaging.

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION

1. Base Level Vibration Test

The input vibration frequency was 4.0 Hz. Immediately after the vibration test was completed, each container was removed from the platform, turned on its side and inspected. No unfavorable distortion or deterioration was observed.

2. Stacking Test

Each container was inspected after the 24-hour period was over. No unfavorable distortion or deterioration was observed.

3. Drop Test

After each drop, the containers were inspected. The contents were completely retained by the container.

REFERENCE MATERIAL

A. United Nation's "Recommendation on the Transportation of Dangerous Goods," ST/SG/AC.10/1, Revision 6.

B. Code of Federal Regulations, Title 49 CFR, Parts 107-178.

C. Bureau of Explosives Tariff No. BOE 6000K Hazardous Materials Regulations of the Department of Transportation by Air, Rail, Highway, Water including Specifications for Shipping Containers.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies)
ATTN: DTIC/FDA
Bldg. 5, Cameron Station
Alexandria, VA 22304-6145

Defense General Supply Center
ATTN: DDRV-TMPA, D. Gay
Richmond, VA 23219

Commander
ATTN: Crane Division (Code 4053)
Naval Surface Warfare Center
Crane, IN 47522-5000

TEST DATA SHEET

POP MARKING:

UN 1A2/Y16/S/**/USA/DOD/NAD

**YEAR LAST PACKED OR MANUFACTURED

DATA SHEET:

Container: Shipping and Storage Container for Mk 125 Mod 2 RATO Rocket Motor

Type: 1A2

Container P/N or NSN:
To Be Determined

Specification Number: DL 1560AS215

Material: Steel

Gross Weight:
16 kg (35 pounds)Dimensions:
8.50" Dia x 30.25" HClosure (Method/Type):
Locking RingTare Weight:
5 kg (11 pounds)

Additional Description: Drum, MS24347

PRODUCT:

Name: See table 1

NSN(s): See table 1

United Nations Number: See table 1

United Nations Packing Group: II

Physical State (Solid, Liquid, or Gas): Solid

Vapor Pressure (Liquids Only): N/A

At 50 °C: N/A

At 55 °C: N/A

Consistency/Viscosity: N/A

Density/Specific Gravity: N/A

Amount Per Container:

Flash Point: N/A

Net Weight: See table 1

TEST PRODUCT:

Name: Sand

Physical State: Solid

Consistency: N/A

Density/Specific Gravity: N/A

Test Pressure (Liquids Only): N/A

Amount Per Container: N/A

Net Weight: 11 kg (24 pounds)

Additional Description:

The net weight includes the current maximum product weight plus an additional 1 kg (2 pounds).

TABLE 1
Products Approved for Shipping in the
Shipping and Storage Container
for Mk 125 Mod 2 RATO Rocket Motor

NALC/ DODIC	NSN	Product Nomenclature	Packing Drawing Number	Haz Class/Div	UN Number	Units/ Cntr	Total Net Weight (lb)	Total Gross Weight (lb)
TBD	TBD	Mk 125 Mod 2 Rocket Motor	DL 1560AS215	3	0186	1	22	33

TBD = To Be Determined